

Product Specifications

70ESN2000TA8T

Cleco's NeoTek™ 70 Series High Torque Corded Electric Nutrunners are engineered to provide superior performance, advance ergonomics, lower total cost of ownership and cost-effective tightening system solutions for demanding high-torque applications.

HIGH TORQUE CORDED NUTRUNNER
775 - 2000 Nm (572 - 1475 ft-lbs)

HIGH TORQUE - 70 SERIES

FEATURES

- Repeatability & accuracy with 2.0 Cm/Cmk at +/- 7%
- 60% faster
- Digital communication for reliable performance
- Internal temperature monitoring
- Configurable LED light rings
- Data logging with on-board tool memory Preventive maintenance alerts
- Configurable multi-function buttons
- Non-contacting, long-lasting switches
- Quarter-turn tool cable connection
- Compatible with:
 - mPro300GCD-NA & mPro300GCD-EMEA & mPro300GCD-APAC
 - mPro400GCD-P & mPro400GCD-SH Controllers
- Total cable length not to exceed 28 meters

SPECIFICATIONS

TORQUE RANGE (Nm)

Min / Max: 775 / 2000

TORQUE RANGE (ft-lb)

Min / Max: 572 / 1475

SPEED

r/min: 32

WEIGHT & DIMENSIONS

Weight 8.7 kg / 19.2 lb
Length 621 mm / 24.4 in
Side to Center 41 mm / 1.6 in
Output Drive 1" Sq. Drive

Country of Origin: Assembled in USA

