

Product Specifications

70EAN1500TA8MT


Cleco's NeoTek™ 70 Series High Torque Coded Electric Nutrunners are engineered to provide superior performance, advance ergonomics, lower total cost of ownership and cost-effective tightening system solutions for demanding high-torque applications.

HIGH TORQUE CORDED NUTRUNNER
375 - 1500 Nm (277 - 1106 ft.-lbs)

HIGH TORQUE - 70 SERIES

FEATURES

- Repeatability & accuracy with 2.0 Cm/Cmk at +/- 7%
- 60% faster
- Digital communication for reliable performance
- Internal temperature monitoring
- Configurable LED light rings
- Data logging with on-board tool memory Preventive maintenance alerts
- Configurable multi-function buttons
- Non-contacting, long-lasting switches
- Quarter-turn tool cable connection
- Compatible with:
 - mPro300GCD-NA & mPro300GCD-EMEA & mPro300GCD-APAC
 - mPro400GCD-P & mPro400GCD-SH Controllers
- Total cable length not to exceed 28 meters



SPECIFICATIONS

TORQUE RANGE (Nm)

Min / Max: 375 / 1500

TORQUE RANGE (ft·lb)

Min / Max: 277 / 1106

SPEED

r/min: 60

WEIGHT & DIMENSIONS

Weight 11.6 kg / 25.5 lb

Length 659 kg / 25.9 in

Side to Center 42 mm / 1.61 in

Output Drive 1" Sq. Drive

Country of Origin: Assembled in USA

