

Product Specifications

70ESN4000UA12MT

Cleco's NeoTek™ 70 Series High Torque Corded Electric Nutrunners are engineered to provide superior performance, advance ergonomics, lower total cost of ownership and cost-effective tightening system solutions for demanding high-torque applications.

HIGH TORQUE CORDED NUTRUNNER
1250 - 4000 Nm (922 - 2950 ft-lbs)

HIGH TORQUE - 70 SERIES

FEATURES

- Repeatability & accuracy with 2.0 Cm/Cmk at +/- 7%
- 60% faster
- Digital communication for reliable performance
- Internal temperature monitoring
- Configurable LED light rings
- Data logging with on-board tool memory Preventive maintenance alerts
- Configurable multi-function buttons
- Non-contacting, long-lasting switches
- Quarter-turn tool cable connection
- Compatible with:
 - mPro300GCD-NA & mPro300GCD-EMEA & mPro300GCD-APAC
 - mPro400GCD-P & mPro400GCD-SH Controllers
- Total cable length not to exceed 28 meters

SPECIFICATIONS

TORQUE RANGE (Nm)

Min / Max: 1250 / 4000

TORQUE RANGE (ft-lb)

Min / Max: 922 / 2950

SPEED

r/min: 18

WEIGHT & DIMENSIONS

Weight 12.8 kg / 28.3 lb

Length 615 mm / 24.2 in

Side to Center 60 mm / 2.3 in

Output Drive 1-1/2" Sq. Drive

Country of Origin: Assembled in USA

