
## Datasheet of 7812 19 19 Flow regulator







## Description

Metal regulators, Bi-directional regulator made of stainless steel, M5x0,8 - M5x0,8

throttle valve, threaded, made of stainless steel, bi-directional: - with female thread, G-thread and metric

- recessed screw
- Throtteling of air supply and exhaust, no non-return function.

- reliable and progressive adjustment with a screwdriver guaranteeing stability of adjustment - strong construction for improved longevity

- ideally suited for aggressive atmospheres or environments submitted to significant chemical or mechanical constraints

## Details

| C:                               | M5x0,8               |
|----------------------------------|----------------------|
| E:                               | 4                    |
| E1:                              | 4                    |
| F:                               | 8                    |
| H min:                           | 22                   |
| H max:                           | 26                   |
| J:                               | 9                    |
| L:                               | 11                   |
| Maximum working pressure in bar: | 10                   |
| Material seal:                   | FKM                  |
| Material adjusting spindle:      | Stainless steel 316l |
| Material body:                   | Stainless steel 316l |
| max. temperature in °C:          | 70                   |
| RoHS compliant:                  | Yes                  |
| Weight in kg:                    | 0,29                 |

## Dimensions

| C:     | M5x0,8 |
|--------|--------|
| E:     | 4      |
| E1:    | 4      |
| F:     | 8      |
| H min: | 22     |
| H max: | 26     |
| J:     | 9      |
| L:     | 11     |