
Datasheet of 7820 00 13 Flow regulator







Description

Metal regulators, regulator in-line made of stainless steel, uni-directional, G1/4 - G1/4

throttle valve, threaded, made of stainless steel, uni-directional:

- for line installation

- Large adjustment screw and lock nut guaranteeing stability of adjustment

- Throtteling of air supply and exhaust, no non-return function.

- ideally suited for aggressive atmospheres or environments submitted to severe chemical or mechanical constraints

Details

| C: | G1/4" | |
|----------------------------------|----------------------|--|
| H min: | 47 | |
| H max: | 52,5 | |
| H1: | 30 | |
| К: | 20 | |
| L: | 40 | |
| L1: | 20 | |
| N: | 30 | |
| T: | 20 | |
| Flow rate in I/min: | 2300 | |
| Bore in mm: | 7 | |
| Maximum working pressure in bar: | 16 | |
| Material seal: | FKM | |
| Material adjusting spindle: | Stainless steel 316l | |
| Material body: | Stainless steel 316l | |
| Material lever: | Stainless steel 316l | |
| Material stem: | Stainless steel 316l | |
| min. temperature in °C: | -15 | |
| max. temperature in °C: | 120 | |
| RoHS compliant: | Yes | |
| Weight in kg: | 0,163 | |

Dimensions

| C: | G1/4" | |
|--------|-------|--|
| H min: | 47 | |
| H max: | 52,5 | |
| H1: | 30 | |
| К: | 20 | |
| L: | 40 | |
| L1: | 20 | |
| N: | 30 | |
| T: | 20 | |

maku Industrie GmbH & Co. KG - Fon: +49 7151/903 95 0 - Fax: +49 7151/903 95 99 - info@maku-industrie.de