

Datasheet of IH709325200/40 Multipurpose hose

Description

Multipurpose transfer hose, black, 15 bar, 6,5 x 13 mm, length 40 m

GST II Black 15 bar is a low pressure multipurpose hose designed to handle air, mild chemicals and water. The EPDM tube compound is specially formulated so to withstand oil mist which is an added value for this typology of products and a real benefit for your stock control. Thanks to this peculiarity it is ideal for air tool lubricant systems where together with air there are traces of oil.

Details

| | |
|-------------------------|--|
| Series: | 7093 |
| Colour: | black |
| Bend radius: | min. 50 mm |
| Material: | EPDM |
| Working temperature: | -40°C up to +100°C |
| Working pressure: | 15 bar |
| Outside calibrated: | No |
| Additional information: | <ul style="list-style-type: none"> • Suitable for oil mist • Reinforcement with synthetic textile yarns |
| Special feature: | Burst pressure value 4:1 |
| Description: | Applications <ul style="list-style-type: none"> • Air tooling • General industrial • Water transfer |
| Medium suitability: | <ul style="list-style-type: none"> • Air • Water • Mild chemicals |
| Weight in kg: | 0,13 |
| Mould coupling: | Yes |
| Item number: | IH709325200/40 |

Dimensions

| | |
|----------------------------|------------|
| Inner diameter: | 6,5 mm |
| Connection 1: | without |
| Connection 2: | without |
| Length in m: | 40 |
| Hose Inner diameter in mm: | 6,5 |
| Outer diameter in mm: | 13 |
| Wall thickness in mm: | 3,25 |
| Bend radius: | min. 50 mm |