

## Datasheet of IH7092100200/40 Multipurpose hose

### Description

Multipurpose transfer hose, red, 15 bar, 25 x 36 mm, length 40 m

GST II Red 15 bar is a low pressure multipurpose hose designed to handle air, mild chemicals and water. The EPDM tube compound is specially formulated so to withstand oil mist which is an added value for this typology of products and a real benefit for your stock control. Thanks to this peculiarity it is ideal for air tool lubricant systems where together with air there are traces of oil.

### Details

Series:	7093
Colour:	red
Bend radius:	min. 200 mm
Material:	EPDM
Working temperature:	-40°C up to +100°C
Working pressure:	15 bar
Outside calibrated:	No
Additional information:	<ul style="list-style-type: none"> <li>• Suitable for oil mist</li> <li>• Reinforcement with synthetic textile yarns</li> </ul>
Special feature:	Burst pressure value 4:1
Description:	Applications <ul style="list-style-type: none"> <li>• Air tooling</li> <li>• General industrial</li> <li>• Water transfer</li> </ul>
Medium suitability:	<ul style="list-style-type: none"> <li>• Air</li> <li>• Water</li> <li>• Mild chemicals</li> </ul>
Weight in kg:	0,69
Mould coupling:	Yes
Item number:	IH7092100200/40

### Dimensions

Inner diameter:	25 mm
Connection 1:	without
Connection 2:	without
Length in m:	40
Hose Inner diameter in mm:	25
Outer diameter in mm:	36
Wall thickness in mm:	5,5
Bend radius:	min. 200 mm