Datasheet of 6801 12 17 Stud fitting

ØD

OF C

DE1



Н

Е

Description

Stud fitting CleanFit®, Brass nickel plated chemical fda brass, 12 mm, G3/8"

In-line connection of tubing to a threaded port. External tightening with a flat spanner or socket wrench, internal adjustment with an Allen key Robust eco-conception, aesthetic design and superior level of cleaneliness for a perfect compatibility

INDUST

RIE

Robust eco-conception, aesthetic design and superior level of cleaneliness for a perfect compatibility Airtight, antistatic packaging Full flow

ASTM G93-03 B 300, ISO 15001, VDI 2083 Conform to CGA G4.1 and DI93/42/EC

Details

ØD:	12 mm
C:	G3/8"
E:	5,5
F:	20
F1:	9
H:	27
Maximum working pressure in bar:	15
Material seal:	EPDM
Material body:	Brass nickel plated chemical fda brass
Material toothed washer:	Stainless steel
min. temperature in °C:	-10
max. temperature in °C:	95
Vacuum resistance in mm Hg:	755
Material:	Brass nickel plated chemical fda brass
RoHS compliant:	Yes
Weight in kg:	0,029

Dimensions

ØD:	12 mm
C:	G3/8"
E:	5,5
F:	20
F1:	9
H:	27

maku Industrie GmbH & Co. KG - Fon: +49 7151/903 95 0 - Fax: +49 7151/903 95 99 - info@maku-industrie.de