
Maku INDUSTRIE

Datasheet of 6866 08 10 Plug-in reducer





Description

Plug-in reducer CleanFit®, Biobased raw materials, 8 mm, 10 mm

In-line connection of tubing of smaller diameter with another push-in fitting Robust eco-conception, aesthetic design and superior level of cleaneliness for a perfect compatibility Airtight, antistatic packaging Full flow 100 % leak-tested, date coding to guarantee quality and traceability ASTM G93-03 B 300, ISO 15001, VDI 2083 Conform to CGA G4.1 and DI93/42/EC

Details

| ØD: | 8 mm | |
|----------------------------------|------------------------|--|
| ØD1: | 10 mm | |
| G: | 13,5 | |
| L: | 48,5 | |
| L1: | 28,5 | |
| Maximum working pressure in bar: | 15 | |
| Material seal: | EPDM | |
| Material body: | Biobased raw materials | |
| Material toothed washer: | Stainless steel | |
| min. temperature in °C: | -10 | |
| max. temperature in °C: | 95 | |
| Vacuum resistance in mm Hg: | 755 | |
| Material: | Biobased raw materials | |
| RoHS compliant: | Yes | |
| Weight in kg: | 0,009 | |

Dimensions

| ØD: | 8 mm |
|------|-------|
| ØD1: | 10 mm |
| G: | 13,5 |
| L: | 48,5 |
| L1: | 28,5 |