


Datasheet of 9064001 – IN-LINE CHECK VALVE SERIES VNR L pipe-pipe Ø=4



Description

Inline check valves, pipe-pipe, Ø4, 0,5 – 12 bar, 80 NI/min flow rate

The VNR L check valve belongs to the LINE ON LINE® family, which means it can be connected to all the other components in series or in parallel.

Available in the version for pipe-pipe connection with two push-in fittings, and in the version for thread-pipe connection with a brass nickel-plated male thread and a push-in fitting. It is still the only check valve with holes for wall mounting

Details

Flow rate in l/min:	80 NI/min (at 6.3 bar, ?P=1 bar)
B:	17,5
C:	10,7
E:	10
Medium suitability:	Filtered, lubricated or unlubricated, compressed air. Lubrication, if used, must be continuous.
Working temperature:	-20 – +60 °C
Working pressure:	0,5 – 12 bar
Recommended pipe:	Rilsan PA 11 – Nylon 6 – Polyamide 12 – Polypropylene.
Weight in kg:	0,01

Dimensions

Connection 1:	Push-in fitting 4 mm outside calibrated
Connection 2:	Push-in fitting 4 mm outside calibrated
Ø:	4
A:	41,8
B:	17,5
C:	10,7
D:	5,6
E:	10
I:	12,8
I1:	16