

Datasheet of 232A0470 ToolReg pressure regulator



Description


ToolReg Regulator with relieving function, outlet pressure 7 bar, supply pressure max. 25 bar, female thread G 1/2, aluminium

In-Line pressure regulator with factory-set outlet pressure, reducing from e.g. 15 bar to 6 bar. With an outlet pressure tolerance of only $\pm 10\%$ *2 it is especially suitable for nailing machines.

Select the pressure regulator according to the desired outlet pressure. The outlet pressure cannot be subsequently adjusted. This safeguards against tampering.

Details

Series:	232
Flow rate in l/min:	2400
Series long:	232
max. inlet pressure:	25 bar
Outlet pressure:	7 bar
Advantages:	<ul style="list-style-type: none"> • Higher safety through lower pressure. Tools and equipment protected against pressure damages. • Cost reduction through substantially reduced air consumption. Longer service life. • Noise reduction for tools.
Additional information:	Relieving at removal of supply pressure.
Working temperature:	0°C up to +80°C
Connection:	Female thread G 1/2
Connection description:	Female thread G 1/2
Material:	Aluminium
Seal description:	Nitrite-butadiene rubber
Surface:	blank finish
Material seal:	NBR
Medium suitability:	compressed air or non-corrosive gases
Weight in kg:	0,075
Hydraulics:	No
Pneumatics:	Yes
Water-resistant:	No



Dimensions

Connection A:	G 1/2
A mm:	30
B mm:	68
SW mm:	27
SW1 mm:	30

