Datasheet of WPN 19 TAB WaterProfi-coupling SLW 19 Quick coupling T R I E





 D
 Mater

 Weigi
 Weigi

 Wate
 Single

 Steckerprofil
 Single

 Two-l
 Self-v

 Safet
 Flat-s

 Dime
 L mm

 D mm
 D mm

Description

WaterProfi-quick coupling with shut-off valve and hose connection 3/4" (19 mm), brass nickel plated, DN 9

Π

WaterProfi quick couplings are completely made of brass MS 58 which offers a more robust and wear resistance vs other couplings made of plastics. The one-hand operation guarantees a simplified work and an optimum ease of use. WaterProfi products are outfitted with O-rings to offerbest sealing characteristics. That means: leakages can be avoided with the coupling system as often seen with pre-mounted compression fittings now in the past.

Details

Series:	WPN
Old order number:	WS 19 TAB
Series long:	WPN
Bore:	DN 9
Maximum working pressure in bar:	PN 16 bar
max. temperature in °C:	+95°C
Shut-Off:	Quick coupling Single Shut-Off
Connection:	Hose barb 19mm LW(3/4")
Material:	Brass nickel plated
Weight in kg:	0,128
Water-resistant:	Yes
Single-hand operation:	Yes
Two-hand operation:	No
Self-venting coupling:	No
Safety locking system:	No
Flat-sealing:	No

Dimensions

L mm:	64
D mm:	28
L1 mm:	22,5