

Datasheet of D1 G1/2RH Oxygen



Description

Plug straight-through, coded system, female thread G 1/2RH, Oxygen, <20 bar, stainless steel

Type D1 for torch side installation

The coupling pin D1 according to EN561, ISO 7289:

- no mixing up by different coding of coupling pins
- prevents accidental disconnection
- coupling pin in stainless steel
- swivel nut in brass 2.0401

Safety elements of the IBEDA Coupling pin D1:

- coding of coupling pins

Details

Length in mm:	47
Series:	D
Gas types:	Oxygen (O), Compressed Air (D), Nitrogen (N), Carbon Dioxide (N), Argon (N), Helium (N)
Series long:	D1
Maximum working pressure in bar:	20 (O, D, N)
Additional information:	Zulassungen / Technische Regeln / Richtlinien
Working temperature:	-20°C up to +70°C
Shut-Off:	Plug Straight-Through
Connection:	Female thread G 1/2RH
Connection description:	Right-hand thread
Connection type:	Female thread
Material:	Stainless steel
Surface:	blank finish
Material connection:	Brass
Weight in kg:	0,042
Coded:	Yes
Water-resistant:	No
Flat-sealing:	No
Hydraulics:	No
Standard product:	No
Mould coupling:	No

Dimensions

Diameter in mm:	21
Length in mm:	47