

Datasheet of D1 G3/8LH Fuel gas



Description

Plug straight-through, coded system, female thread G 3/8LH, Fuel gas, <20 bar, stainless steel

Type D1 for torch side installation

The coupling pin D1 according to EN561, ISO 7289:

- no mixing up by different coding of coupling pins
- prevents accidental disconnection
- coupling pin in stainless steel
- swivel nut in brass 2.0401

Safety elements of the IBEDA Coupling pin D1:

- coding of coupling pins

Details

Length in mm:	47
Series:	D
Gas types:	Acetylene (A), Hydrogen (H), Industrial Gas (C), Natural Gas (Methane M), Propane (P)
Series long:	D1
Maximum working pressure in bar:	1,5 (A), 20 (H, C, M, P)
Additional information:	Zulassungen / Technische Regeln / Richtlinien
Working temperature:	-20°C up to +70°C
Shut-Off:	Plug Straight-Through
Connection:	Female thread G 3/8LH
Connection description:	Left-hand thread
Connection type:	Female thread
Material:	Stainless steel
Surface:	blank finish
Material connection:	Brass
Weight in kg:	0,042
Coded:	Yes
Water-resistant:	No
Flat-sealing:	No
Hydraulics:	No
Standard product:	No
Mould coupling:	No

Dimensions

Diameter in mm:	21
Length in mm:	47