

Datasheet of D2 9mm Fuel gas



Description

Plug straight-through, coded system, hose barb 9mm (3/8), Fuel gas, <20 bar, stainless steel

Type D2 for tapping point or in-hose

The coupling pin D2 according to EN561, ISO 7289:

- no mixing up by different coding of coupling pins
- prevents accidental disconnection
- coupling pin in stainless steel

Safety elements of the IBEDA Coupling pin D2:

- coding of coupling pins

Details

Length in mm:	55
Series:	D
Gas types:	Acetylene (A), Hydrogen (H), Industrial Gas (C), Natural Gas (Methane M), Propane (P), Oxygen (O), Compressed Air (D), Nitrogen (N), Carbon Dioxide (N), Argon (N) , Helium (N)
Series long:	D2
Maximum working pressure in bar:	1,5 (A), 20 (H, C, M, P, O, D, N)
Additional information:	Zulassungen / Technische Regeln / Richtlinien
Working temperature:	-20°C up to +70°C
Shut-Off:	Plug Straight-Through
Connection:	Hose barb 9mm LW(3/8")
Connection type:	Hose barb
Material:	Stainless steel
Surface:	blank finish
Material connection:	Edelstahl
Weight in kg:	0,017
Coded:	Yes
Water-resistant:	No
Flat-sealing:	No
Hydraulics:	No
Standard product:	No
Mould coupling:	No

Dimensions

Diameter in mm:	12,3
Length in mm:	55