

## Datasheet of D4 G3/8LH Fuel gas



### Description

Plug straight-through, coded system, male thread G 3/8LH, Fuel gas, <20 bar, stainless steel

#### Type D4 for tapping point or in-hose

The coupling pin D4 according to EN561, ISO 7289:

- no mixing up by different coding of coupling pins
- prevents accidental disconnection
- coupling pin in stainless steel

Safety elements of the IBEDA Coupling pin D4:

- coding of coupling pins

### Details

Length in mm:	46,5
Series:	D
Gas types:	Acetylene (A), Hydrogen (H), Industrial Gas (C), Natural Gas (Methane M), Propane (P)
Series long:	D4
Maximum working pressure in bar:	1,5 (A), 20 (H, C, M, P)
Additional information:	Zulassungen / Technische Regeln / Richtlinien
Working temperature:	-20°C up to +70°C
Shut-Off:	Plug Straight-Through
Connection:	Male thread G 3/8LH
Connection description:	Left-hand thread
Connection type:	Male thread
Material:	Stainless steel
Surface:	blank finish
Material connection:	Edelstahl
Weight in kg:	0,029
Coded:	Yes
Water-resistant:	No
Flat-sealing:	No
Hydraulics:	No
Standard product:	No
Mould coupling:	No

### Dimensions

Diameter in mm:	17
Length in mm:	46,5