
## Datasheet of CLBPW04Q-EU CellClutch Connect cordless torque control pistol grip nutrunner











### Description

Cordless pistol grip nutrunner with torque control, torque 1,1 - 4 Nm, speed 177 - 1500 1/min, 1/4" hex quick change, WiFi/Bluetooth

# CellClutch cordless assembly tools enable simple, programmable torque control for your production.

CellClutch<sup>™</sup> offers a torque control for functional screwdriving cases, and this is programmable for up to 7 levels to avoid errors when screwing in. The Tools have speed regulation and ensure long-term repeatability and accuracy in the screwing process.

• Reduction of operating errors – The presetting of the torque on the tool side and the screw status display using colored lights (green = OK, red = NOK) make it easier to handle the device correctly. Avoid errors when screwing in and double screwing with adjustable speeds and programmable screwing sequences.

• Benefits of connectivity – The optional WiFi (2.4 & 5 GHz) and Bluetooth Low Energy (v4.2) connectivity of the Connect models allows you to adjust settings, access real-time reports, data is tracked and counts are performed when the device is connected to the mPro Controller platform. A connection with a smartphone app is in preparation.

• Uniform Battery Platform – The Milwaukee® M18 Red Lithium battery is compatible with the entire battery products range. This enables economical storage of accessories.

• **Uncomplicated commissioning** – Setting the desired torque is a quick and easy process that consists of 3 steps: carry out a screw connection, read the torque and then make adjustments. Another screw connection serves to confirm that the target torque has been achieved.

• Speed control – The speed settings can be changed quickly and easily according to the requirements of the screwing job.

• Ergonomic design – The battery operation means there is no need for annoying cables and hoses. The low weight makes working easier.

• Software included - The software is already included when you purchase the tool at no additional cost.

Note: You can find suitable batteries and chargers in the accessories tab.

#### Details

Output:	1/4" quick-action chuck	
Length in mm:	217,5	
Maximum torque in Nm:	4	
Drehmoment min. in Nm:	1,1	
Precision:	Cmk > 1.67 +/- 10%	
Scope of delivery:	Hanging bail Torque adjustment tool Torque detection rings black, gray, blue Socket, battery and charger are not included	
Additional information:	Software available as a free download	
RoHS compliant:	Yes	
Weight in kg:	1,1	

### Dimensions

Height in mm:	209
Side to center in mm:	29
Length in mm:	217,5