





Datasheet of 48KBAW13DPX Quick coupling with male thread



Description

Quick coupling double shut-off, male thread G 1/4, nominal diameter 7, <10 bar, POM (Delrin), seal NBR

Coupling series made of POM and PVDF has been developed for use in the medical, chemical, food handling, pharmaceutical and laboratory technology industries. The system is also available in a solid plastic design (RectuChem+). Here the metal springs are replaced by springs made of PEEK, an extremely resistant synthetic material.

Details

| | |
|---|---|
| Series: | 48 |
| Series long: | 48KB |
| Bore in mm: | 7 |
| Bore area in mm²: | 38 |
| Advantages: | Coupling system with single-hand operation. The color coding of the coupling and plug offers a guarantee for avoiding mix-ups between media when coupling. The coupling is also available with no valve for a straightthrough system. |
| Working pressure: | PB = 10 bar (at 20°C) maximum static working pressure with safety factor 4 to 1. |
| Working temperature: | -20°C up to +80°C depending on the medium. |
| Shut-Off: | Quick coupling Double Shut-Off |
| Connection: | Male thread 1/4" |
| Connection description: | Male pipe thread of Whitworth form ISO 228 1/4" |
| Connection type: | Male thread |
| Material: | POM (Delrin) |
| Material description: | POM (Delrin) |
| Seal description: | Nitrite-butadiene rubber |
| Surface: | blank finish |
| Material connection: | POM, black |
| Material valve body: | POM, black |
| Material sleeve: | POM, black |
| Material valve: | POM, black |
| Material spring snap ring: | Stainless steel AISI 316Ti |
| Material balls/pins: | POM, black |
| Material seal: | Perbunan® |
| Weight in kg: | 0,0283 |
| Self-venting coupling: | No |
| Safety locking system: | No |
| Single-hand operation: | Yes |
| Two-hand operation: | No |
| Ball locking: | No |
| Pin lock: | No |
| Ultra-FLO-valve: | No |
| Vacuum suitable: | Yes |
| Water-resistant: | Yes |
| Flat-sealing: | No |
| Suitable breath / respiratory protection: | No |
| Pressure eliminator: | No |
| Hydraulics: | No |
| Pneumatics: | Yes |
| Standard product: | No |
| Mould coupling: | No |

Dimensions

| | |
|---------------|-------|
| Connection A: | G 1/4 |
| D mm: | 26 |
| L mm: | 70,5 |
| L1 mm: | 9 |
| SW mm: | 21 |