



# Datasheet of 48KFTF04FVP Quick coupling with hose barb



## Description

Quick coupling straight-through, hose barb 4mm (3/16), nominal diameter 7, <8 bar, PVDF, seal FKM

Coupling series made of POM and PVDF has been developed for use in the medical, chemical, food handling, pharmaceutical and laboratory technology industries. The system is also available in a solid plastic design (RectuChem+). Here the metal springs are replaced by springs made of PEEK, an extremely resistant synthetic material.

## Details

|   |   |
|---|---|
| Series:                                   | 48  |
| Series long:                              | 48KF  |
| Bore in mm:                               | 7   |
| Bore area in mm <sup>2</sup> :            | 38  |
| Advantages:                               | Coupling system with single-hand operation. The color coding of the coupling and plug offers a guarantee for avoiding mix-ups between media when coupling. The coupling is also available with no valve for a straightthrough system. |
| Working pressure:                         | PB = 8 bar (PVDF with springs made of steel) PB = 8 bar (PVDF with springs made of PEEK), maximum static working pressure with safety factor 4 to 1.  |
| Working temperature:                      | -20°C up to +120°C depending on the medium.   |
| Shut-Off:                                 | Quick coupling Straight-Through   |
| Connection:                               | Hose barb 4mm LW(3/16")   |
| Connection description:                   | Hose barb 4mm LW(3/16")   |
| Connection type:                          | Hose barb   |
| Material:                                 | PVDF  |
| Material description:                     | PVDF  |
| Seal description:                         | Fluororubber  |
| Surface:                                  | Pressure springs made of PEEK   |
| Material connection:                      | PVDF, white   |
| Material valve body:                      | PVDF, white   |
| Material sleeve:                          | PVDF, white   |
| Material spring snap ring:                | PEEK 450G   |
| Material balls/pins:                      | PEEK 450G   |
| Material seal:                            | Viton®  |
| Weight in kg:                             | 0,0274  |
| Self-venting coupling:                    | No  |
| Safety locking system:                    | No  |
| Single-hand operation:                    | Yes   |
| Two-hand operation:                       | No  |
| Ball locking:                             | No  |
| Pin lock:                                 | No  |
| Ultra-FLO-valve:                          | No  |
| Vacuum suitable:                          | Yes   |
| Water-resistant:                          | No  |
| Flat-sealing:                             | No  |
| Suitable breath / respiratory protection: | No  |
| Pressure eliminator:                      | No  |
| Hydraulics:                               | No  |
| Pneumatics:                               | Yes   |
| Standard product:                         | No  |
| Mould coupling:                           | No  |

## Dimensions