



Datasheet of PA060/100/02 PA-hose



Description

PA-hose rot, RECTULASTIC, 4,0 x 6,0 mm, length 100 m

RECTULASTIC hoses from Nycoil for safer, more efficient air power transmission.

Details

Series:	RECTULASTIC
Colour:	red
Material:	Nylon 12 (PA)
Working temperature:	-40°C up to +90°C
Working pressure:	see chart
Outside calibrated:	Yes
Advantages:	<ul style="list-style-type: none"> - quick assembly possible - straight hoses ideal for Push-In-System - light weight - low pressure drop - different colors for identification - good storage possibility due to box packing (straight hoses) - high abrasion resistance - self-retracting. Coiled Hose automatically recoils to a fraction of its working length - small bending diameter - resistant to oil, gasoline, grease and abrasion
Physical properties:	<ul style="list-style-type: none"> - light weight (specific weight 9x lower as copper) - wide temperature range - high resistance against moisture - saltwater insensitive - long service time
Mechanical properties:	<ul style="list-style-type: none"> - high vibration prevention - perfect abrasion resistance - high compression characteristics - low flow reduction for all kind of media - precise tolerances - constant solidity
Medium suitability:	<ul style="list-style-type: none"> - compressed air - lubrication grease/oil - gasoline - hydraulic - vacuum - chemicals (on request) - foodstuff (on request)
Weight in kg:	2,151

Dimensions

Inner diameter:	4,0 mm
Connection 1:	without
Connection 2:	without
Length in m:	100
Hose Inner diameter in mm:	4,0
Outer diameter in mm:	6,0
Wall thickness in mm:	1