


Datasheet of 3693 08 13 L-stud coupling





Description

LF 3600 - Brass special - Industrie and food, L-stud coupling, Brass nickel plated chemical fda brass, 2 x 8 mm - G1/4

In line connection of 2 tubes at a 90° angle to a threaded port. Solid construction and compact design. Excellent resistance to corrosion. Individual unit quality control and dating in order to guarantee quality and traceability. Components meet FDA standard and 1935/2004/EC regulation and comply RoHS.

Details

ØD:	8 mm
C:	G1/4"
E:	6,5
F:	16
G:	15
H:	26,5
H1:	23,5
J:	10
L:	31
Maximum working pressure in bar:	30
Material seal ring:	Brass nickel plated chemical fda brass
Material seal:	FKM
Material body:	Brass nickel plated chemical fda brass
Material threaded fitting:	Brass nickel plated chemical fda brass
Material release button:	Brass nickel plated chemical fda brass
min. temperature in °C:	-20
max. temperature in °C:	150
Vacuum resistance in mm Hg:	755
Special feature:	schwenkbar
RoHS compliant:	Yes
Weight in kg:	0,044

Dimensions

ØD:	8 mm
C:	G1/4"
ØD: C: E: F: G:	6,5
F:	16
G:	15
H:	26,5 23,5
H1:	23,5
J:	10
L:	31