


Datasheet of 3816 60 00 Straight bulkhead connector





Description

LF 3800 / LF 3900 - Stainless steel, straight bulkhead connector, Stainless steel 316l, 3/8 - 3/8

Connects 2 tubes through a panel.

- materials: Stainless steel, sealings: FKM.
- stainless steel components and FKM seals for use in aggressive environments
- strong construction and compact
- hygienic design aimed at reducing retention zones for safe and easy cleaning (Ra < 0,8 surface)
- permitting permanent contact with foodstuffs
- individual unit quality control and dating in order to guarantee quality and traceability
- materials conforming to FDA and 1934/2004 CE standards

Details

| ØD: | 3/8" |
|----------------------------------|----------------------|
| F: | 27 |
| F1: | 22 |
| L1: | 22,098 |
| L2: | 27,432 |
| T: | 20,574 |
| Maximum working pressure in bar: | 30 |
| Material seal ring: | Stainless steel 316l |
| Material seal: | FKM |
| Material body: | Stainless steel 316l |
| Material release button: | Stainless steel 303 |
| Material union nut: | Stainless steel 316l |
| min. temperature in °C: | -20 |
| max. temperature in °C: | 120 |
| RoHS compliant: | Yes |
| Weight in kg: | 0,051 |

Dimensions

| ØD: | 3/8" |
|-----|--------|
| F: | 27 |
| F1: | 22 |
| L1: | 22,098 |
| L2: | 27,432 |
| T: | 20,574 |