


## Datasheet of 3899 08 10 Stud elbow





## Description

LF 3800 / LF 3900 - Stainless steel, stud elbow, Stainless steel 316l, 8 mm - G1/8

Connection of tubing at a  $90\ensuremath{^\circ}$  angle to a threaded port.

- materials: Stainless steel, sealings: FKM.
- stainless steel components and FKM seals for use in aggressive environments
- strong construction and compact
- hygienic design aimed at reducing retention zones for safe and easy cleaning (Ra < 0,8 surface)
- permitting permanent contact with foodstuffs
- individual unit quality control and dating in order to guarantee quality and traceability
- materials conforming to FDA and 1934/2004 CE standards

## Details

ØD:	8 mm
C:	G1/8"
F:	14
G:	15
H:	35
L:	25
Maximum working pressure in bar:	20
Material seal ring:	Stainless steel 316l
Material seal:	FKM
Material body:	Stainless steel 316l
Material threaded fitting:	Stainless steel 316l
Material release button:	Stainless steel 303
min. temperature in °C:	-20
max. temperature in °C:	120
Special feature:	schwenkbar
RoHS compliant:	Yes
Weight in kg:	0,039

## Dimensions

ØD:	8 mm
C:	G1/8"
F:	14
G:	15
H:	35
L:	25