

SP06/075 PA-coiled hose


PA-coiled hose blue, RECTULASTIC, 4,8 x 6,3 mm



Product description

RECTULASTIC hoses from Nycoil for safer, more efficient air power transmission.

More images



Product properties

Outer diameter in mm	6,3
Working pressure	see chart
Weight in kg	0,1449
Material	Nylon 12 (PA)
Mechanical properties	- high vibration prevention_x000D_ - perfect abrasion resistance_x000D_ - high compression characteristics_x000D_ - low flow reduction for all kind of media_x000D_ - precise tolerances_x000D_ - constant solidity
Medium suitability	- compressed air - lubrication grease/oil - gasoline - hydraulic - vacuum - chemicals (on request) - foodstuff (on request)
Physical properties	- light weight (specific weight 9x lower as copper)_x000D_ - wide temperature range_x000D_ - high resistance against moisture_x000D_ - saltwater insensitive_x000D_ - long service time
Hose outlet	radial
Series	RECTULASTIC
Working temperature	-40°C up to +90°C
Additional information	without connectors

Dimensions

Connection 1	without
Connection 2	without
Number of turns	45
Colour	blue
Inner diameter	4,8 mm
Max. working length in m	7,5
Hose Inner diameter in mm	4,8
Wall thickness in mm	0,75
Outer coil diameter in mm	75