

SP12/025/K+S PA-coiled hose


PA-coiled hose blue with coupling and plug (Type 26), RECTULASTIC, 9,5 x 11,8 mm



Product description

RECTULASTIC hoses from Nycoil for safer, more efficient air power transmission.

More images



Product properties

Outer diameter in mm	11,8
Outside calibrated	No
Special feature	with quick coupling and plug (Typ 26)
Working pressure	see chart
Colour	blue
Mould coupling	No
Weight in kg	0,34
Material	Nylon 12 (PA)
Mechanical properties	- high vibration prevention_x000D_ - perfect abrasion resistance_x000D_ - high compression characteristics_x000D_ - low flow reduction for all kind of media_x000D_ - precise tolerances_x000D_ - constant solidity
Medium suitability	- compressed air - lubrication grease/oil - gasoline - hydraulic - vacuum - chemicals (on request) - foodstuff (on request)
Physical properties	- light weight (specific weight 9x lower as copper)_x000D_ - wide temperature range_x000D_ - high resistance against moisture_x000D_ - saltwater insensitive_x000D_ - long service time
Professional recommendation	Complete
Hose outlet	radial
Series	RECTULASTIC
Working temperature	-20°C up to +70°C
Additional information	Both sides completely integrated with coupling and plug (Type 26) with spring guard

Dimensions

Connection 1	Kupplung Typ 26
Connection 2	Plug type 26
Number of turns	8
Inner diameter	9,5 mm
Max. working length in m	2,5
Hose Inner diameter in mm	9,5
Wall thickness in mm	1,15
Outer coil diameter in mm	140