

PG10/075/DV PU-coiled hose


PU-coiled hose translucent blue with swivelling thread male thread G 1/4, SUPERBRAID, 6,3 x 9,5 mm



Product description

Superbraid polyurethane recoil hose is extruded with an inner braid for additional strength. This „integral piece“ process eliminates the need of bonding individual layers of hoses, braiding and cover which tend to separate overtime due to bending, flexing and pulsating. Superbraid combines the durability of bulkier hoses with the kink resistance and elasticity of polyurethane to make a tough, long lasting hose that is user friendly. Superbraid can be used with either our barb and sleeve fittings or reusable polyurethane fittings.

More images



Product properties

Outer diameter in mm	9,5
Special feature	with svivelling thread
Working pressure	see chart
Colour	lightblue-clear
Weight in kg	0,49
Hardness	85 Shore A
Material	Polyurethane (PU)
Hose outlet	axial
Series	SUPERBRAID
Working temperature	-40°C up to +75°C
Additional information	with woven fabric inlay completely assembled with swivel fittings

Dimensions

Connection 1	Male thread G 1/4"
Connection 2	Male thread G 1/4"
Inner diameter	6,3 mm
Length in m	7,5
Hose Inner diameter in mm	6,3
Wall thickness in mm	1,6
Outer coil diameter in mm	42