

22SFAW13MXX Plug with male thread




Plug straight-through, male thread G 1/4, nominal diameter 5,5, <35 bar, brass



Product description

Coupling system with single-hand operation. UltraFlo valve for optimum flow and low pressure drop. Specially suited to use with gaseous media in industry. The steel sleeve counters oscillating forces. The high insertion depth is guaranteed by an optimised plug guide.

More images



Product properties

Shut-off	Plug Straight-Through
Connection	Male thread 1/4"
Connection description	Male pipe thread of Whitworth form ISO 228 1/4"
Connection type	Male thread
Suitable breath / respiratory protection	No
Seal	Without Seal
Working pressure	35 bar maximum static working pressure with safety factor 4 to 1.
Pressure eliminator	No
Single-hand operation	Yes
Self-venting coupling	No
Flat-sealing	No
Mould coupling	No
Weight in kg	0,022
Hydraulics	No
Compatibility	RECTUS 14, PARKER 50
Ball locking	No
Material	Brass
Material description	Brass CuZn39Pb3 2.0401 (except sleeve)
Bore area in mm ²	25
Bore in mm	5,5
Surface	blank finish
Pneumatics	Yes
Series	22
Series long	22SF
Safety locking system	No
Standard product	No
Pin lock	No
Working temperature	-20°C up to +100°C (NBR) -40°C up to +120/150°C (EPDM) -15°C up to +200°C (FKM) depending on the medium.
Ultra-FLO-valve	No
Vacuum suitable	Yes
Advantages	One-hand operation. The high insertion depth is guaranteed by an optimised plug guide. UltraFlo valve.
Water-resistant	No
Two-hand operation	No

Dimensions

Connection A	G 1/4
L mm	41
L1 mm	12
SW mm	14