

19SFTF10SXN Plug with hose barb





Plug straight-through, hose barb 10mm, nominal diameter 5,5, <35 bar, steel nickel plated



Product description

English industrial profile. Coupling system with single-hand operation. UltraFlo valve for optimum flow and low pressure drop. Robust coupling in slim design mainly for pneumatic applications. The steel sleeve counters oscillating forces. The high insertion depth is guaranteed by an optimised plug guide.

More images



Product properties

Shut-off	Plug Straight-Through
Connection	Hose barb 10mm
Connection description	Hose barb 10mm
Connection type	Hose barb
Suitable breath / respiratory protection	No
Seal	Without Seal
Working pressure	35 bar maximum static working pressure with safety factor 4 to 1.
Pressure eliminator	No
Single-hand operation	Yes
Self-venting coupling	No
Flat-sealing	No
Mould coupling	No
Weight in kg	0,0197
Hydraulics	No
Ball locking	No
Material	Steel nickel-plated
Material description	Steel 9SMnPb28K 1.0718
Bore area in mm ²	25
Bore in mm	5,5
Surface	nickel plated
Pneumatics	Yes
Series	19
Series long	19SF
Safety locking system	No
Standard product	No
Pin lock	No
Working temperature	-20°C up to +100°C (NBR) -40°C up to +120/150°C (EPDM) -15°C up to +200°C (FKM) depending on the medium.
Ultra-FLO-valve	No
Vacuum suitable	Yes
Advantages	One-hand operation. The high insertion depth is guaranteed by an optimised plug guide. UltraFlo valve.
Water-resistant	No
Two-hand operation	No

Dimensions

Connection A	10 mm
D mm	12
L mm	60
L1 mm	25