

23SFIW17SXN Plug with female thread




Plug straight-through, female thread G 3/8, nominal diameter 5,5, <35 bar, steel nickel plated



Product description

1/4 industrial coupling according to ISO 6150 B and US MIL-SPEC 4109. Especially suitable for use with gaseous media in industry. Coupling system with single-hand operation. UltraFlo valve for optimum flow and low pressure drop. Steel sleeve counters oscillating forces. The high insertion depth is guaranteed by an optimised plug guide.

More images



Product properties

Shut-off	Plug Straight-Through
Connection	Female thread 3/8"
Connection description	Female pipe thread of Whitworth form ISO 228 3/8"
Connection type	Female thread
Suitable breath / respiratory protection	No
Seal	Without Seal
Working pressure	35 bar maximum static working pressure with safety factor 4 to 1.
Pressure eliminator	No
Single-hand operation	Yes
Self-venting coupling	No
Flat-sealing	No
Mould coupling	No
Weight in kg	0,025
Hydraulics	No
Compatibility	INDUSTR. INTERCHANGE 1/4" US-MIL-SPEC-C-4109 ISO 6150 RECTUS 24, RECTUS 1400/1423 TEMA 1400 PARKER 20 1/4" + 30 1/4"
Ball locking	No
Material	Steel nickel-plated
Material description	Steel 9SMnPb28K 1.0718
Bore area in mm ²	25
Bore in mm	5,5
Surface	nickel plated
Pneumatics	Yes
Series	23
Series long	23SF
Safety locking system	No
Standard product	No
Pin lock	No
Working temperature	-20°C up to +100°C (NBR) -40°C up to +120/150°C (EPDM) -15°C up to +200°C (FKM) depending on the medium.
Ultra-FLO-valve	No
Vacuum suitable	Yes
Advantages	One-hand operation. The high insertion depth is guaranteed by an optimised plug guide. UltraFlo valve.
Water-resistant	No
Two-hand operation	No

Dimensions

Connection A	G 3/8
L mm	36
L1 mm	9
SW mm	19