

## 25SBIM16RVX Plug with female thread




Plug double shut-off, female thread M 16 x 1,5, nominal diameter 7,4, <35 bar, stainless steel AISI 303, seal FKM



### Product description

Universal industrial coupling with standard European profile for use with gaseous, liquid and aggressive medio. Coupling system with single-hand operation. UltraFlo valve for optimum flow and low pressure drop. The series stands out for its robust design and long service life even with the harshest use. The collar design minimises damage to the valve body.

### More images



## Product properties

|                                          |                                                                                                             |
|------------------------------------------|-------------------------------------------------------------------------------------------------------------|
| Shut-off                                 | Plug Double Shut-Off                                                                                        |
| Connection                               | Female thread M 16 x 1,5                                                                                    |
| Connection description                   | Female thread M 16 x 1,5                                                                                    |
| Connection type                          | Female thread                                                                                               |
| Suitable breath / respiratory protection | No                                                                                                          |
| Seal                                     | FKM                                                                                                         |
| Seal description                         | Fluororubber                                                                                                |
| Working pressure                         | 35 bar maximum static working pressure with safety factor 4 to 1.                                           |
| Pressure eliminator                      | No                                                                                                          |
| Single-hand operation                    | Yes                                                                                                         |
| Self-venting coupling                    | No                                                                                                          |
| Flat-sealing                             | No                                                                                                          |
| Mould coupling                           | No                                                                                                          |
| Weight in kg                             | 0,0505                                                                                                      |
| Hydraulics                               | No                                                                                                          |
| Ball locking                             | No                                                                                                          |
| Material                                 | stainless steel AISI 303                                                                                    |
| Material description                     | stainless steel AISI 303                                                                                    |
| Bore area in mm <sup>2</sup>             | 42                                                                                                          |
| Bore in mm                               | 7,4                                                                                                         |
| Surface                                  | blank finish                                                                                                |
| Pneumatics                               | Yes                                                                                                         |
| Series                                   | 25                                                                                                          |
| Series long                              | 25SB                                                                                                        |
| Safety locking system                    | No                                                                                                          |
| Standard product                         | No                                                                                                          |
| Pin lock                                 | No                                                                                                          |
| Working temperature                      | -20°C up to +100°C (NBR) -40°C up to +120/150°C (EPDM) -15°C up to +200°C (FKM) depending on the medium.    |
| Ultra-FLO-valve                          | No                                                                                                          |
| Vacuum suitable                          | No                                                                                                          |
| Advantages                               | One-hand operation. Robust structure. UltraFlo valve. The collar design minimises damage to the valve body. |
| Water-resistant                          | No                                                                                                          |
| Material connection                      | stainless steel AISI 303                                                                                    |
| Material seal                            | Viton®                                                                                                      |
| Material spring snap ring                | stainless steel AISI 301                                                                                    |
| Material valve                           | stainless steel AISI 303                                                                                    |
| Two-hand operation                       | No                                                                                                          |

## Dimensions

|              |            |
|--------------|------------|
| Connection A | M 16 x 1,5 |
|--------------|------------|