

25SBKK12MPX Plug with hose nut and spring guard




Plug double shut-off, with hose nut and spring guard 9 x 12 mm, nominal diameter 7,4, <35 bar, brass, seal NBR



Product description

Universal industrial coupling with standard European profile. Coupling system with single-hand operation. UltraFlo valve for optimum flow and low pressure drop. The series stands out for its robust design and long service life even with the harshest use.

More images



Product properties

Shut-off	Plug Double Shut-Off
Connection	Tube nut with spring guard 9 x 12 mm
Connection description	Tube nut with spring guard 9 x 12 mm
Connection type	Connection nut
Suitable breath / respiratory protection	No
Seal	NBR
Seal description	Nitrite-butadiene rubber
Working pressure	35 bar maximum static working pressure with safety factor 4 to 1.
Pressure eliminator	No
Single-hand operation	Yes
Self-venting coupling	No
Flat-sealing	No
Mould coupling	No
Weight in kg	0,099
Hydraulics	No
Ball locking	No
Material	Brass
Material description	Brass CuZn39Pb3 2.0401 (except sleeve)
Bore area in mm ²	42
Bore in mm	7,4
Surface	blank finish
Pneumatics	Yes
Series	25
Series long	25SB
Safety locking system	No
Standard product	No
Pin lock	No
Working temperature	-20°C up to +100°C (NBR) -40°C up to +120/150°C (EPDM) -15°C up to +200°C (FKM) 0°C up to +316°C (FFKM) depending on the medium.
Ultra-FLO-valve	No
Vacuum suitable	No
Advantages	One-hand operation. Robust structure. UltraFlo valve. The collar design minimises damage to the valve body.
Water-resistant	Yes
Material connection	Brass
Material seal	Perbunan®
Material spring snap ring	stainless steel AISI 301
Material valve	Brass
Two-hand operation	No

Dimensions

Connection A	9 x 12 mm
G mm	M 16 x 1
L mm	150
L1 mm	8,5
L2 mm	8,5
SW mm	19