

25SFKO12RXX Plug with hose nut




Plug straight-through, with hose nut 9 x 12 mm, nominal diameter 7,8, <35 bar, stainless steel AISI 303



Product description

Universal industrial coupling with standard European profile for use with gaseous, liquid and aggressive medio. Coupling system with single-hand operation. UltraFlo valve for optimum flow and low pressure drop. The series stands out for its robust design and long service life even with the harshest use. The collar design minimises damage to the valve body.

More images



Product properties

Shut-off	Plug Straight-Through
Connection	with tube nut 9 x 12 mm
Connection description	with tube nut 9 x 12 mm
Connection type	Connection nut
Suitable breath / respiratory protection	No
Seal	Without Seal
Working pressure	35 bar maximum static working pressure with safety factor 4 to 1.
Pressure eliminator	No
Single-hand operation	Yes
Self-venting coupling	No
Flat-sealing	No
Mould coupling	No
Weight in kg	0,0309
Hydraulics	No
Compatibility	RECTUS 26 European standard profiles
Ball locking	No
Material	stainless steel AISI 303
Material description	stainless steel AISI 303
Bore area in mm ²	48
Bore in mm	7,8
Surface	blank finish
Pneumatics	Yes
Series	25
Series long	25SF
Safety locking system	No
Standard product	No
Pin lock	No
Working temperature	-20°C up to +100°C (NBR) -40°C up to +120/150°C (EPDM) -15°C up to +200°C (FKM) depending on the medium.
Ultra-FLO-valve	No
Vacuum suitable	No
Advantages	One-hand operation. Robust structure. UltraFlo valve.
Water-resistant	Yes
Two-hand operation	No

Dimensions

Connection A	9 x 12 mm
G mm	M 16 x 1
L mm	42
L1 mm	9
L2 mm	8
SW mm	17