

1600KETF10SPN Quick coupling self-venting



Safety coupling with a self-venting system, hose barb 10mm, nominal diameter 7,8, <12 bar, steel nickel plated, seal NBR



Product description

Safety coupling with a self-venting system. Selfventing takes place during disconnection – no risk of pressurised hoses being tossed around. When the sleeve is pulled back, the plug is released yet remains locked in. The coupling valve closes and the air is vented from the air line at the same time. Only then, by operating the sleeve again, can uncoupling take place safely. The system fulfils the requirements of ISO 4414 – increased safety standards in the workplace. DIN EN 983. UltraFlo valve for optimum flow and low pressure drop.

More images



Product properties

Shut-off	Quick coupling Self-Venting system
Connection	Hose barb 10mm
Connection description	Hose barb 10mm
Connection type	Hose barb
Suitable breath / respiratory protection	No
Seal	NBR
Seal description	Nitrite-butadiene rubber
Working pressure	2-12 bar maximum static working pressure with safety factor 4 to 1.
Pressure eliminator	No
Single-hand operation	Yes
Self-venting coupling	Yes
Flat-sealing	No
Mould coupling	No
Weight in kg	0,001
Hydraulics	No
Ball locking	Yes
Material	Steel nickel-plated
Material description	Steel 9SMnPb28K 1.0718
Bore area in mm ²	48
Bore in mm	7,8
Surface	nickel plated
Pneumatics	Yes
Professional recommendation	Self-Venting
Series	1600
Series long	1600KE
Safety locking system	Yes
Standard product	No
Pin lock	No
Working temperature	-20°C up to +100°C (NBR) depending on the medium.
Ultra-FLO-valve	Yes
Vacuum suitable	Yes
Advantages	No risk of pressurised hoses being tossed around.
Water-resistant	No
Material connection	Brass nickel plated
Material seal	Perbunan®
Material sleeve	steel hardened
Material spring snap ring	stainless steel AISI 301
Material balls/pins	Stainless steel AISI 420
Material valve	Brass
Material valve body	steel zinc plated, thick film passivated
Additional information	Reliable functioning can only be guaranteed in conjunction with original Parker Rectus plugs made of steel.
Two-hand operation	No

Dimensions

Connection A	10 mm
D mm	26
L mm	79,5
L1 mm	25
SW mm	19