

## 21SBAM14RVX Plug with male thread





Plug double shut-off, male thread M 14 x 1,5, nominal diameter 5, <35 bar, stainless steel AISI 303, seal FKM



### Product description

Mini industrial coupling with the world's most popular profile in this nominal diameter. Above average flow performance for liquid and gaseous medio. Coupling system with single-hand operation. Small dimensions and large band width in materials and valve variants.

### More images



## Product properties

|                                          |                                                                                                          |
|------------------------------------------|----------------------------------------------------------------------------------------------------------|
| Shut-off                                 | Plug Double Shut-Off                                                                                     |
| Connection                               | Male thread M 14 x 1,5                                                                                   |
| Connection description                   | Male thread M 14 x 1,5                                                                                   |
| Connection type                          | Male thread                                                                                              |
| Suitable breath / respiratory protection | No                                                                                                       |
| Seal                                     | FKM                                                                                                      |
| Seal description                         | Fluororubber                                                                                             |
| Working pressure                         | 35 bar maximum static working pressure with safety factor 4 to 1.                                        |
| Pressure eliminator                      | No                                                                                                       |
| Single-hand operation                    | Yes                                                                                                      |
| Self-venting coupling                    | No                                                                                                       |
| Flat-sealing                             | No                                                                                                       |
| Mould coupling                           | No                                                                                                       |
| Weight in kg                             | 0,03                                                                                                     |
| Hydraulics                               | No                                                                                                       |
| Ball locking                             | No                                                                                                       |
| Material                                 | stainless steel AISI 303                                                                                 |
| Material description                     | stainless steel AISI 303                                                                                 |
| Bore area in mm <sup>2</sup>             | 20                                                                                                       |
| Bore in mm                               | 5                                                                                                        |
| Surface                                  | blank finish                                                                                             |
| Pneumatics                               | Yes                                                                                                      |
| Series                                   | 21                                                                                                       |
| Series long                              | 21SB                                                                                                     |
| Safety locking system                    | No                                                                                                       |
| Standard product                         | No                                                                                                       |
| Pin lock                                 | No                                                                                                       |
| Working temperature                      | -20°C up to +100°C (NBR) -40°C up to +120/150°C (EPDM) -15°C up to +200°C (FKM) depending on the medium. |
| Ultra-FLO-valve                          | No                                                                                                       |
| Vacuum suitable                          | Yes                                                                                                      |
| Advantages                               | One-hand operation. Small dimensions.                                                                    |
| Water-resistant                          | No                                                                                                       |
| Material connection                      | stainless steel AISI 303                                                                                 |
| Material seal                            | Viton®                                                                                                   |
| Material spring snap ring                | stainless steel AISI 301                                                                                 |
| Material valve                           | stainless steel AISI 303                                                                                 |
| Two-hand operation                       | No                                                                                                       |

## Dimensions

|              |            |
|--------------|------------|
| Connection A | M 14 x 1,5 |
| L mm         | 43         |
| L1 mm        | 10         |
| SW mm        | 17         |