

21SBTS06MPN Plug panel mount with hose barb




Plug double shut-off, panel mount with hose barb 6mm (1/4), nominal diameter 5, <35 bar, brass nickel plated, seal NBR



Product description

Mini industrial coupling with the world's most popular profile in this nominal diameter. Above average flow performance for liquid and gaseous medio. Coupling system with single-hand operation. Small dimensions and large band width in materials and valve variants.

More images



Product properties

Shut-off	Plug Double Shut-Off
Connection	Hose barb in Panel mount 6mm LW(1/4")
Connection description	Hose barb in Panel mount 6mm LW(1/4")
Connection type	Hose barb
Suitable breath / respiratory protection	No
Seal	NBR
Seal description	Nitrite-butadiene rubber
Working pressure	35 bar maximum static working pressure with safety factor 4 to 1.
Pressure eliminator	No
Single-hand operation	Yes
Self-venting coupling	No
Flat-sealing	No
Mould coupling	No
Weight in kg	0,044
Hydraulics	No
Ball locking	No
Material	Brass nickel plated
Material description	Brass CuZn39Pb3 2.0401 (except sleeve)
Bore area in mm ²	20
Bore in mm	5
Surface	nickel plated
Pneumatics	Yes
Series	21
Series long	21SB
Safety locking system	No
Standard product	No
Pin lock	No
Working temperature	-20°C up to +100°C (NBR) -40°C up to +120/150°C (EPDM) -15°C up to +200°C (FKM) 0°C up to +316°C (FFKM) depending on the medium.
Ultra-FLO-valve	No
Vacuum suitable	Yes
Advantages	One-hand operation. Small dimensions.
Water-resistant	Yes
Material connection	Brass nickel plated
Material seal	Perbunan®
Material spring snap ring	stainless steel AISI 301
Material valve	Brass
Two-hand operation	No

Dimensions

Connection A	6 mm
B mm	4
G mm	M 12 x 1
L mm	64
L1 mm	17
L2 mm	14
SW mm	14
SW1 mm	17