

21SFAW17MXX Plug with male thread




Plug straight-through, male thread G 3/8, nominal diameter 5, <35 bar, brass



Product description

Mini industrial coupling with the world's most popular profile in this nominal diameter. Above average flow performance for liquid and gaseous medio. Coupling system with single-hand operation. Small dimensions and large band width in materials and valve variants.

More images



Product properties

Shut-off	Plug Straight-Through
Connection	Male thread 3/8"
Connection description	Male pipe thread of Whitworth form ISO 228 3/8"
Connection type	Male thread
Suitable breath / respiratory protection	No
Seal	Without Seal
Working pressure	35 bar maximum static working pressure with safety factor 4 to 1.
Pressure eliminator	No
Single-hand operation	Yes
Self-venting coupling	No
Flat-sealing	No
Mould coupling	No
Weight in kg	0,024
Hydraulics	No
Compatibility	RECTUS 90
Ball locking	No
Material	Brass
Material description	Brass CuZn39Pb3 2.0401 (except sleeve)
Bore area in mm ²	20
Bore in mm	5
Surface	blank finish
Pneumatics	Yes
Professional recommendation	Pneumatic standard
Series	21
Series long	21SF
Safety locking system	No
Standard product	Yes
Pin lock	No
Working temperature	-20°C up to +100°C (NBR) -40°C up to +120/150°C (EPDM) -15°C up to +200°C (FKM) 0°C up to +316°C (FFKM) depending on the medium.
Ultra-FLO-valve	No
Vacuum suitable	Yes
Advantages	One-hand operation. Small dimensions. All variants are compatible.
Water-resistant	Yes
Two-hand operation	No

Dimensions

Connection A	G 3/8
L mm	28
L1 mm	9
SW mm	17, 19