

## 21SFTS04MXN6 Plug color coded


Plug straight-through, coded system (6 = blue, hexagon), panel mount with hose barb 4mm (3/16), nominal diameter 5, <35 bar, brass nickel plated



### Product description

Coded industrial coupling system developed on the basis of series 21 with above-average flow rate for liquid and gaseous media. Coupling system with single-hand operation. The mechanical coding of the coupling and plug offers a guarantee for avoiding mix-ups between media when coupling, which is complemented by the color coding of the anodised sleeves. Double shut-off version available on request.

### More images



## Product properties

|                                          |                                                                   |
|------------------------------------------|-------------------------------------------------------------------|
| Shut-off                                 | Plug Straight-Through                                             |
| Connection                               | Hose barb in Panel mount 4mm LW(3/16")                            |
| Connection description                   | Hose barb in Panel mount 4mm LW(3/16")                            |
| Connection type                          | Hose barb                                                         |
| Suitable breath / respiratory protection | No                                                                |
| Seal                                     | Without Seal                                                      |
| Working pressure                         | 35 bar maximum static working pressure with safety factor 4 to 1. |
| Pressure eliminator                      | No                                                                |
| Single-hand operation                    | Yes                                                               |
| Self-venting coupling                    | No                                                                |
| Flat-sealing                             | No                                                                |
| Mould coupling                           | No                                                                |
| Weight in kg                             | 0,032                                                             |
| Hydraulics                               | No                                                                |
| Coded                                    | Yes                                                               |
| Coding                                   | 6 = blue, hexagon                                                 |
| Ball locking                             | No                                                                |
| Material                                 | Brass nickel plated                                               |
| Material description                     | Brass CuZn39Pb3 2.0401 (except sleeve)                            |
| Bore area in mm <sup>2</sup>             | 20                                                                |
| Bore in mm                               | 5                                                                 |
| Surface                                  | nickel plated                                                     |
| Pneumatics                               | Yes                                                               |
| Professional recommendation              | Coding                                                            |
| Series                                   | 21                                                                |
| Series long                              | 21SF                                                              |
| Safety locking system                    | No                                                                |
| Standard product                         | No                                                                |
| Pin lock                                 | No                                                                |
| Working temperature                      | -20°C up to +100°C (NBR)                                          |
| Ultra-FLO-valve                          | No                                                                |
| Vacuum suitable                          | Yes                                                               |
| Advantages                               | Quality product. One-hand operation.                              |
| Water-resistant                          | Yes                                                               |
| Two-hand operation                       | No                                                                |

## Dimensions

|              |       |
|--------------|-------|
| Connection A | 4 mm  |
| B mm         | 4     |
| G mm         | M10x1 |
| L mm         | 63    |
| L1 mm        | 17    |
| L2 mm        | 14    |
| SW mm        | 17    |
| SW1 mm       | 14    |