

21KATF08MEX8 Quick coupling with hose barb




Quick coupling single shut-off, coded system (8 = red, octagonal), hose barb 8mm (5/16), nominal diameter 5, <35 bar, brass, seal EPDM



Product description

Coded industrial coupling system developed on the basis of series 21 with above-average flow rate for liquid and gaseous media. Coupling system with single-hand operation. The mechanical coding of the coupling and plug offers a guarantee for avoiding mix-ups between media when coupling, which is complemented by the color coding of the anodised sleeves. Double shut-off version available on request.

More images



Product properties

Shut-off	Quick coupling Single Shut-Off
Connection	Hose barb 8mm LW(5/16")
Connection description	Hose barb 8mm LW(5/16")
Connection type	Hose barb
Suitable breath / respiratory protection	No
Seal	EPDM
Seal description	Ethylene-propylene-diene rubber
Working pressure	35 bar maximum static working pressure with safety factor 4 to 1.
Pressure eliminator	No
Single-hand operation	Yes
Self-venting coupling	No
Flat-sealing	No
Mould coupling	No
Weight in kg	0,0335
Hydraulics	No
Coded	Yes
Coding	8 = red, octagonal
Ball locking	Yes
Material	Brass
Material description	Brass CuZn39Pb3 2.0401 (except sleeve)
Bore area in mm ²	20
Bore in mm	5
Surface	blank finish
Pneumatics	Yes
Professional recommendation	Coding
Series	21
Series long	21KA
Safety locking system	No
Standard product	No
Pin lock	No
Working temperature	-20°C up to +100°C (NBR)
Ultra-FLO-valve	No
Vacuum suitable	Yes
Advantages	Quality product. One-hand operation.
Water-resistant	Yes
Material connection	Brass
Material sleeve	Brass
Material spring snap ring	stainless steel AISI 301
Material balls/pins	Stainless steel AISI 420
Material valve	Brass
Material valve body	Brass
Two-hand operation	No

Dimensions

Connection A	8 mm
D mm	16
L mm	69
L1 mm	17
SW mm	14