

21KBKK06MVN Quick coupling with hose nut and spring guard




Quick coupling double shut-off, with hose nut and spring guard 4 x 6 mm, nominal diameter 5, <35 bar, brass nickel plated, seal FKM



Product description

Mini industrial coupling with the world's most popular profile in this nominal diameter. Above average flow performance for liquid and gaseous medio. Coupling system with single-hand operation. Small dimensions and large band width in materials and valve variants.

More images



Product properties

Shut-off	Quick coupling Double Shut-Off
Connection	Tube nut with spring guard 4 x 6 mm
Connection description	Tube nut with spring guard 4 x 6 mm
Connection type	Connection nut
Suitable breath / respiratory protection	No
Seal	FKM
Seal description	Fluororubber
Working pressure	35 bar maximum static working pressure with safety factor 4 to 1.
Pressure eliminator	No
Single-hand operation	Yes
Self-venting coupling	No
Flat-sealing	No
Mould coupling	No
Weight in kg	0,041
Hydraulics	No
Ball locking	Yes
Material	Brass nickel plated
Material description	Brass CuZn39Pb3 2.0401 (except sleeve)
Bore area in mm ²	20
Bore in mm	5
Surface	nickel plated
Pneumatics	Yes
Series	21
Series long	21KB
Safety locking system	No
Standard product	No
Pin lock	No
Working temperature	-20°C up to +100°C (NBR) -40°C up to +120/150°C (EPDM) -15°C up to +200°C (FKM) 0°C up to +316°C (FFKM) depending on the medium.
Ultra-FLO-valve	No
Vacuum suitable	Yes
Advantages	One-hand operation. Small dimensions.
Water-resistant	No
Material connection	Brass nickel plated
Material seal	Viton®
Material sleeve	Brass nickel plated
Material spring snap ring	stainless steel AISI 301
Material balls/pins	Stainless steel AISI 420
Material valve	Brass
Material valve body	Brass nickel plated
Two-hand operation	No

Dimensions

Connection A	4 x 6 mm
D mm	16
G mm	M 10 x 1
L mm	125
L1 mm	7
L2 mm	6
SW mm	14