

20SBKS06RVX Plug with panel mount





Plug double shut-off, panel mount 4 x 6 mm, nominal diameter 2,7, <35 bar, stainless steel
AISI 303, seal FKM/FPM



Product description

Mini industrial coupling with internationally used profile. Frequent use in medical technology and chemistry/pharmacy. Coupling system with single-hand operation. High flow despite small dimensions plus many applications with a variety of medio.

More images



Product properties

Shut-off	Plug Double Shut-Off
Connection	Panel mount 4 x 6 mm
Connection description	Panel mount without spring guard 4 x 6 mm
Connection type	Connection nut
Suitable breath / respiratory protection	No
Seal	FKM/FPM
Seal description	Fluororubber
Working pressure	35 bar maximum static working pressure with safety factor 4 to 1.
Pressure eliminator	No
Single-hand operation	Yes
Self-venting coupling	No
Flat-sealing	No
Mould coupling	No
Weight in kg	0,017
Hydraulics	No
Ball locking	No
Material	stainless steel AISI 303
Material description	stainless steel AISI 303
Bore area in mm ²	5
Bore in mm	2,7
Surface	blank finish
Pneumatics	Yes
Series	20
Series long	20SB
Safety locking system	No
Standard product	No
Pin lock	No
Working temperature	-20°C up to +100°C (NBR) -40°C up to +120/150°C (EPDM) -15°C up to +200°C (FKM) depending on the medium.
Ultra-FLO-valve	No
Vacuum suitable	Yes
Advantages	One-hand operation. Small dimensions. Low pressure Drop.
Water-resistant	No
Material connection	stainless steel AISI 303
Material seal	Viton®
Material spring snap ring	stainless steel AISI 301
Material valve	stainless steel AISI 303
Two-hand operation	No

Dimensions

Connection A	4 x 6 mm
B mm	3,5
G mm	M 8 x 0,5
L mm	47
L1 mm	7
L2 mm	17
SW mm	12
SW1 mm	12