

13SFAK21SXN Plug with male thread




Plug straight-through, male thread R 1/2, nominal diameter 7,5, <35 bar, steel nickel plated



Product description

Robust brass coupling with Japanese industrial profile. Coupling system with single-hand operation. Above average flow volumes and structure resistant to the effects of external forces.

More images



Product properties

Shut-off	Plug Straight-Through
Connection	Male thread 1/2"
Connection description	Male tapered thread of Whitworth form DIN 2999 1/2"
Connection type	Male thread
Suitable breath / respiratory protection	No
Seal	Without Seal
Working pressure	35 bar maximum static working pressure with safety factor 4 to 1.
Pressure eliminator	No
Single-hand operation	Yes
Self-venting coupling	No
Flat-sealing	No
Mould coupling	No
Weight in kg	0,051
Hydraulics	No
Compatibility	RECTUS 03
Ball locking	No
Material	Steel nickel-plated
Material description	Steel 9SMnPb28K 1.0718
Bore area in mm ²	45
Bore in mm	7,5
Surface	nickel plated
Pneumatics	Yes
Series	13
Series long	13SF
Safety locking system	No
Standard product	No
Pin lock	No
Working temperature	-20°C up to +100°C (NBR) -40°C up to +120/150°C (EPDM) -15°C up to +200°C (FKM) depending on the medium.
Ultra-FLO-valve	No
Vacuum suitable	Yes
Advantages	One-hand operation. Corrosion free.
Water-resistant	No
Two-hand operation	No

Dimensions

Connection A	R 1/2
L mm	44
L1 mm	17
SW mm	22