

41KFTF19MPN Quick coupling with hose barb




Quick coupling straight-through, hose barb 19mm (3/4), nominal diameter 10, <35 bar, brass nickel plated, seal NBR



Product description

Brass coupling with no valve for applications with liquids in the pressure range up to 35 bar. The couplings are corrosion resistant. The system stands out for a high flow with minimal pressure drop.

More images



Product properties

Shut-off	Quick coupling Straight-Through
Connection	Hose barb 19mm LW(3/4")
Connection description	Hose barb 19mm LW(3/4")
Connection type	Hose barb
Suitable breath / respiratory protection	No
Seal	NBR
Seal description	Nitrite-butadiene rubber
Working pressure	35 bar maximum static working pressure with safety factor 4 to 1.
Pressure eliminator	No
Single-hand operation	Yes
Self-venting coupling	No
Flat-sealing	No
Mould coupling	No
Weight in kg	0,0594
Hydraulics	No
Compatibility	RECTUS 27
Ball locking	Yes
Material	Brass nickel plated
Material description	Brass CuZn39Pb3 2.0401 (except sleeve)
Bore area in mm²	80
Bore in mm	10
Surface	nickel plated
Pneumatics	Yes
Professional recommendation	Water
Series	41
Series long	41KF
Safety locking system	No
Standard product	No
Pin lock	No
Working temperature	-20°C up to +100°C (NBR) -40°C up to +120/150°C (EPDM) -15°C up to +200°C (FKM) depending on the medium.
Ultra-FLO-valve	No
Vacuum suitable	Yes
Advantages	Non-corrosive. High flow. Minimal pressure drop.
Water-resistant	Yes
Material connection	Brass nickel plated
Material seal	Perbunan®
Material sleeve	Brass nickel plated
Material spring snap ring	stainless steel AISI 301
Material balls/pins	1.3541
Material valve body	Brass nickel plated
Two-hand operation	No

Dimensions

Connection A	19 mm
D mm	25
L mm	48,5
L1 mm	25