

38SBTF13MPX Plug with hose barb





Plug double shut-off, hose barb 13mm (1/2), nominal diameter 15, <35 bar, brass, seal NBR



Product description

Compact industrial coupling system in brass for use with numerous gaseous and liquid medio. UltraFlo valve for optimum flow and low pressure drop.

More images



Product properties

Shut-off	Plug Double Shut-Off
Connection	Hose barb 13mm LW(1/2")
Connection description	Hose barb 13mm LW(1/2")
Connection type	Hose barb
Suitable breath / respiratory protection	No
Seal	NBR
Seal description	Nitrite-butadiene rubber
Working pressure	35 bar maximum static working pressure with safety factor 4 to 1.
Pressure eliminator	No
Single-hand operation	Yes
Self-venting coupling	No
Flat-sealing	No
Mould coupling	No
Weight in kg	0,2661
Hydraulics	No
Ball locking	No
Material	Brass
Material description	Brass CuZn39Pb3 2.0401 (except sleeve)
Bore area in mm ²	175
Bore in mm	15
Surface	blank finish
Pneumatics	Yes
Series	38
Series long	38SB
Safety locking system	No
Standard product	No
Pin lock	No
Working temperature	-20°C up to +100°C (NBR) -40°C up to +120/150°C (EPDM) -15°C up to +200°C (FKM) 0°C up to +316°C (FFKM) depending on the medium.
Ultra-FLO-valve	No
Vacuum suitable	Yes
Advantages	Compact design. Extremely high flow rate. UltraFlo valve.
Water-resistant	Yes
Material connection	Brass
Material seal	Perbunan®
Material spring snap ring	stainless steel AISI 301
Material valve	Brass
Two-hand operation	No

Dimensions

Connection A	13 mm
L mm	103
L1 mm	28
SW mm	34