

38SFTF16MXX Plug with hose barb




Plug straight-through, hose barb 16mm, nominal diameter 15, <35 bar, brass



Product description

Compact industrial coupling system in brass for use with numerous gaseous and liquid medio. UltraFlo valve for optimum flow and low pressure drop.

More images



Product properties

Shut-off	Plug Straight-Through
Connection	Hose barb 16mm
Connection description	Hose barb 16mm
Connection type	Hose barb
Suitable breath / respiratory protection	No
Seal	Without Seal
Working pressure	35 bar maximum static working pressure with safety factor 4 to 1.
Pressure eliminator	No
Single-hand operation	Yes
Self-venting coupling	No
Flat-sealing	No
Mould coupling	No
Weight in kg	0,1074
Hydraulics	No
Ball locking	No
Material	Brass
Material description	Brass CuZn39Pb3 2.0401 (except sleeve)
Bore area in mm²	175
Bore in mm	15
Surface	blank finish
Pneumatics	Yes
Series	38
Series long	38SF
Safety locking system	No
Standard product	No
Pin lock	No
Working temperature	-20°C up to +100°C (NBR) -40°C up to +120/150°C (EPDM) -15°C up to +200°C (FKM) 0°C up to +316°C (FFKM) depending on the medium.
Ultra-FLO-valve	No
Vacuum suitable	Yes
Advantages	Compact design. Extremely high flow rate. UltraFlo valve.
Water-resistant	Yes
Two-hand operation	No

Dimensions

Connection A	16 mm
D mm	30
L mm	73
L1 mm	36