

## TA38 Pressure release valve


Pressure release valve female-/male thread G 3/8, max. 250 bar



### Product description

Produced for hydraulic systems where in line quick connect couplings are used. The system pressure built up between the hydraulic unit and the coupling would not allow mechanical coupling.

### More images



#### Product properties

|                                 |                                                                                                                                                                                                            |
|---------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Connection type                 | Female / Male thread                                                                                                                                                                                       |
| Seal                            | NBR                                                                                                                                                                                                        |
| Working pressure                | max. 250 bar                                                                                                                                                                                               |
| Weight in kg                    | 0,463                                                                                                                                                                                                      |
| Hydraulics                      | Yes                                                                                                                                                                                                        |
| Maximum working pressure in bar | 250                                                                                                                                                                                                        |
| Professional recommendation     | Hydraulics                                                                                                                                                                                                 |
| Series                          | DEV                                                                                                                                                                                                        |
| Series long                     | DEV                                                                                                                                                                                                        |
| Working temperature             | up to max. +90°C depending on the medium.                                                                                                                                                                  |
| Valve                           | Brass                                                                                                                                                                                                      |
| Advantages                      | The Pressure Relief Valve can be mounted directly in the main inflow line so that all downstream pipe or hose lines where quick connect couplings or plugs are installed at the ends can be depressurised. |
| Material T-distributor          | Steel, zinc-plated, passivated, sealed                                                                                                                                                                     |

#### Dimensions

|               |        |
|---------------|--------|
| Connection A  | G 3/8" |
| Connection A1 | G 3/8" |
| D mm          | 33     |
| L mm          | 62     |
| SW mm         | 21     |