

## 10SFAR10MXX Plug with male thread 90° angled



Plug straight-through, male thread 90° M 10 x 1, nominal diameter 6, <15 bar, brass



### Product description

The 10, 11 and 12 Rectus Moldtite coupling series were especially developed for connecting coolant lines and injection moulds. These stand out for their convenient, singlehanded operation and a reliable O-ring seal. Widely used in Europe.

### More images



## Product properties

|                                          |                                                                        |
|------------------------------------------|------------------------------------------------------------------------|
| Shut-off                                 | Plug Straight-Through                                                  |
| Connection                               | Male thread 90° angled M 10 x 1                                        |
| Connection description                   | Male thread 90° angled M 10 x 1                                        |
| Connection type                          | Male thread                                                            |
| Suitable breath / respiratory protection | No                                                                     |
| Seal                                     | Without Seal                                                           |
| Working pressure                         | PB = 15 bar maximum static working pressure with safety factor 4 to 1. |
| Pressure eliminator                      | No                                                                     |
| Single-hand operation                    | Yes                                                                    |
| Self-venting coupling                    | No                                                                     |
| Flat-sealing                             | No                                                                     |
| Mould coupling                           | Yes                                                                    |
| Weight in kg                             | 0,0189                                                                 |
| Hydraulics                               | No                                                                     |
| Ball locking                             | No                                                                     |
| Material                                 | Brass                                                                  |
| Material description                     | Brass CuZn39Pb3 2.0401 (except sleeve)                                 |
| Bore area in mm <sup>2</sup>             | 30                                                                     |
| Bore in mm                               | 6                                                                      |
| Surface                                  | blank finish                                                           |
| Pneumatics                               | No                                                                     |
| Professional recommendation              | Cooling Injection Moulds                                               |
| Series                                   | 10                                                                     |
| Series long                              | 10SF                                                                   |
| Safety locking system                    | No                                                                     |
| Standard product                         | No                                                                     |
| Pin lock                                 | No                                                                     |
| Working temperature                      | -15°C up to +200°C (FKM) depending on the medium                       |
| Ultra-FLO-valve                          | No                                                                     |
| Vacuum suitable                          | Yes                                                                    |
| Water-resistant                          | Yes                                                                    |
| Two-hand operation                       | No                                                                     |

## Dimensions

|              |       |
|--------------|-------|
| Connection A | G 1/8 |
| D mm         | 9     |
| L mm         | 27    |
| L1 mm        | 9     |
| L2 mm        | 28,5  |
| SW mm        | 11    |