

10VNXX24MXX Extension nipple




Extension nipple straight-through, without thread 10 mm, nominal diameter 6, <15 bar, brass



Product description

The 10, 11 and 12 Rectus Moldtite coupling series were especially developed for connecting coolant lines and injection moulds. These stand out for their convenient, singlehanded operation and a reliable O-ring seal. Widely used in Europe.

More images



Product properties

Shut-off	Plug Straight-Through
Connection	without thread 10 mm
Connection description	Pipe without thread outer diameter 10 mm
Connection type	without thread
Suitable breath / respiratory protection	No
Seal	Without Seal
Working pressure	PB = 15 bar maximum static working pressure with safety factor 4 to 1.
Pressure eliminator	No
Single-hand operation	Yes
Self-venting coupling	No
Flat-sealing	No
Mould coupling	Yes
Weight in kg	0,1004
Hydraulics	No
Ball locking	No
Material	Brass
Material description	Brass CuZn39Pb3 2.0401 (except sleeve)
Bore area in mm ²	30
Bore in mm	6
Surface	blank finish
Pneumatics	No
Professional recommendation	Cooling Injection Moulds
Series	10
Series long	10VN
Safety locking system	No
Standard product	No
Pin lock	No
Working temperature	-15°C up to +200°C (FKM) depending on the medium
Ultra-FLO-valve	No
Vacuum suitable	Yes
Water-resistant	Yes
Two-hand operation	No

Dimensions

Connection A	10 mm
D mm	9
L mm	240
L1 mm	220
SW mm	11