

11SFAR13MXN Plug with male thread 90° angled



Plug straight-through, male thread 90° G 1/4, nominal diameter 9, <15 bar, brass nickel plated



Product description

The 10, 11 and 12 Rectus Moldtite coupling series were especially developed for connecting coolant lines and injection moulds. These stand out for their convenient, singlehanded operation and a reliable O-ring seal. Widely used in Europe.

More images



Product properties

Shut-off	Plug Straight-Through
Connection	Male thread 90° angled 1/4"
Connection description	Male thread 90° angled 1/4"
Connection type	Male thread
Suitable breath / respiratory protection	No
Seal	Without Seal
Working pressure	PB = 15 bar maximum static working pressure with safety factor 4 to 1.
Pressure eliminator	No
Single-hand operation	Yes
Self-venting coupling	No
Flat-sealing	No
Mould coupling	Yes
Weight in kg	0,0386
Hydraulics	No
Ball locking	No
Material	Brass nickel plated
Material description	Brass CuZn39Pb3 2.0401 (except sleeve)
Bore area in mm²	63
Bore in mm	9
Surface	nickel plated
Pneumatics	No
Professional recommendation	Cooling Injection Moulds
Series	11
Series long	11SF
Safety locking system	No
Standard product	No
Pin lock	No
Working temperature	-15°C up to +200°C (FKM) depending on the medium
Ultra-FLO-valve	No
Vacuum suitable	Yes
Water-resistant	Yes
Two-hand operation	No

Dimensions

Connection A	G 1/4
D mm	13,5
L mm	34
L1 mm	11
L2 mm	32
SW mm	15