

## 11SFTF09MXX Plug with hose barb




Plug straight-through, hose barb 9mm (3/8), nominal diameter 9, <15 bar, brass



### Product description

The 10, 11 and 12 Rectus Moldtite coupling series were especially developed for connecting coolant lines and injection moulds. These stand out for their convenient, singlehanded operation and a reliable O-ring seal. Widely used in Europe.

### More images



## Product properties

|                                          |                                                                        |
|------------------------------------------|------------------------------------------------------------------------|
| Shut-off                                 | Plug Straight-Through                                                  |
| Connection                               | Hose barb 9mm LW(3/8")                                                 |
| Connection description                   | Hose barb 9mm LW(3/8")                                                 |
| Connection type                          | Hose barb                                                              |
| Suitable breath / respiratory protection | No                                                                     |
| Seal                                     | Without Seal                                                           |
| Working pressure                         | PB = 15 bar maximum static working pressure with safety factor 4 to 1. |
| Pressure eliminator                      | No                                                                     |
| Single-hand operation                    | Yes                                                                    |
| Self-venting coupling                    | No                                                                     |
| Flat-sealing                             | No                                                                     |
| Mould coupling                           | Yes                                                                    |
| Weight in kg                             | 0,07                                                                   |
| Hydraulics                               | No                                                                     |
| Ball locking                             | No                                                                     |
| Material                                 | Brass                                                                  |
| Material description                     | Brass CuZn39Pb3 2.0401 (except sleeve)                                 |
| Bore area in mm <sup>2</sup>             | 63                                                                     |
| Bore in mm                               | 9                                                                      |
| Surface                                  | blank finish                                                           |
| Pneumatics                               | No                                                                     |
| Professional recommendation              | Cooling Injection Moulds                                               |
| Series                                   | 11                                                                     |
| Series long                              | 11SF                                                                   |
| Safety locking system                    | No                                                                     |
| Standard product                         | No                                                                     |
| Pin lock                                 | No                                                                     |
| Working temperature                      | -15°C up to +200°C (FKM) depending on the medium                       |
| Ultra-FLO-valve                          | No                                                                     |
| Vacuum suitable                          | Yes                                                                    |
| Water-resistant                          | Yes                                                                    |
| Two-hand operation                       | No                                                                     |

## Dimensions

|              |      |
|--------------|------|
| Connection A | 9 mm |
| D mm         | 13,5 |
| L mm         | 41   |
| L1 mm        | 25   |