

12SBAW26MVN Plug with male thread




Plug double shut-off, male thread G 3/4, nominal diameter 13, <15 bar, brass nickel plated, seal FKM



Product description

The 10, 11 and 12 Rectus Moldtite coupling series were especially developed for connecting coolant lines and injection moulds. These stand out for their convenient, singlehanded operation and a reliable O-ring seal. Widely used in Europe.

More images



Product properties

Shut-off	Plug Double Shut-Off
Connection	Male thread 3/4"
Connection description	Male pipe thread of Whitworth form ISO 228 3/4"
Connection type	Male thread
Suitable breath / respiratory protection	No
Seal	FKM
Seal description	Fluororubber
Working pressure	PB = 15 bar maximum static working pressure with safety factor 4 to 1.
Pressure eliminator	No
Single-hand operation	Yes
Self-venting coupling	No
Flat-sealing	No
Mould coupling	Yes
Weight in kg	0,0919
Hydraulics	No
Ball locking	No
Material	Brass nickel plated
Material description	Brass CuZn39Pb3 2.0401 (except sleeve)
Bore area in mm ²	133
Bore in mm	13
Surface	nickel plated
Pneumatics	No
Professional recommendation	Cooling Injection Moulds
Series	12
Series long	12SB
Safety locking system	No
Standard product	No
Pin lock	No
Working temperature	-15°C up to +200°C (FKM) depending on the medium
Ultra-FLO-valve	No
Vacuum suitable	Yes
Water-resistant	Yes
Material seal	Viton®
Material spring snap ring	stainless steel AISI 301
Material valve	Brass
Two-hand operation	No

Dimensions

Connection A	G 3/4
D mm	19
L mm	51
L1 mm	16
SW mm	27